

Vores serviceteknikere kører i hele Danmark

# OMNIE

**Al-Powered Robot Floor Cleaner** for High-Dynamic Environments











### **Key Features**

#### ( OmniVision

360° camera coverage with 360° object detection and a bird's-eye view for enhanced obstacle avoidance and precise navigation.



#### ( OmniClean

Pre-sweeping FREE\*, scrubbing with a wider 520 mm cleaning path while simultaneously swallowing up to 10L trash per hour.

\*Available soc



#### (iii) OmniLiDAR

360° LiDAR coverage, optimized for large highly dynamic industrial environments.



#### (A) OmniSpotCleaning

Precisely identifying and cleaning both dry and wet waste powered by Al deep learning.



#### **Applicable Flooring Types**







Artificial Stone



Ceramic



Concrete



PVC



Epoxy



## Specification\*

	Disc Brush	Roller Brush
Net Weight	157 kg   346.1 lb	148 kg   326.3 lb
Cleaning Width	520 mm   20.5 in	406 mm   16 in With side brushes: 780 mm   30.7 in
Max. Cleaning Efficiency (Theoretical)	Scrubbing: 2,621 m²/h   28,212 ft²/h Dust Mopping: 3,604 m²/h   38,793 ft²/h	Scrubbing: 2,046 m²/h   22,023 ft²/h Sweeping: 3,931 m²/h   42,313 ft²/h Dust Mopping: 3,604 m²/h   38,793 ft²/h
Dimension (L×W×H)	810×700×1,070 mm   31.9×27×42.1 in	
Max. Runtime	Scrubbing 3 h, Dust Mopping 8 h, Sweeping 8 h	
Charging Time		2 h
Clean/Waste Water Tank	33L / 24 L   8.7 gal / 6.3 gal	
Gradeability		4.6°
Min. Pass Width	800 mm   31.5 in	
Min. U-turn Width	1,100 mm   43.3 in	
Max. Cleaning Speed		1.4 m/s   3.1 mph
Sensor System	3D LiDAR, 2D LiDAR, 3D Depth Camera, RGB Camera, Anti-Collision, Anti-Drop	

# OMNI **POWER**FOR A NEXT-LEVEL CLEAN