

SCRUBBER 50

AI-Powered Robotic Floor Scrubber
for Medium to Large Spaces

(Certified to **IEC 63327** 2021 Standards)



Key Features

Versatile Cleaning

3-in-1 Solution

Integrates scrubbing, sweeping, and dust mopping in a single solution.

2 Main Brush Options

Choose between a disc brush or a roller brush to suit your specific cleaning requirements.

AI-Powered Perception

Spot Cleaning Mode

Proactively detects and cleans waste using RGB camera and AI algorithms, bringing up to 400% efficiency improvement.

Smart Obstacle Avoidance

Recognizes people and obstacles, making advanced behavior decisions based on their types and characteristics.

Sustainability

Water Recycling

Features a built-in multi-stage filtration system that recycles and reuses water, reducing freshwater consumption by approximately 80%.

Energy Efficient

Delivers up to 10 hours of runtime in the Spot Cleaning mode, reducing energy consumption by approximately 75%.

Effortless Maintenance

Quick-Release Cleaning Components

The squeegee assembly and filter components feature a quick-release design for tool-free disassembly and reassembly within seconds.

Docking Stations

Optional workstation for self-docking power charging and water management.


Applicable Flooring Types



Natural Stone




Artificial Stone




Ceramic



Concrete



PVC



Epoxy



Specification *

	Disc Brush	Roller Brush
Net Weight	157 kg 346.1 lb	148 kg 326.3 lb
Cleaning Width	460 mm 18.1 in	406 mm 16 in With side brushes: 780 mm 30.7 in
Edge Cleaning Capability	40 mm 1.6 in	40 mm 1.6 in With side brushes: 0 mm 0 in
Brush Pressure	25 kg 55 lb	18 kg 39.7 lb
Trash Tray Capacity		2×0.6 L 2×0.16 gal
Max. Runtime	Scrubbing 3 h Dust Mopping 8 h	Scrubbing 3 h Dust Mopping 6 h
Max. Scrubbing Efficiency (Theoretical)	1,987 m ² /h 21,388 ft ² /h	1,754 m ² /h 18,880 ft ² /h
Practical Cleaning Efficiency	500-1,300 m ² /h 5,382-13,993 ft ² /h	
Dimension (L×W×H)	810×700×1,070 mm 31.9×27×42.1 in	
Charging Time	2 h	
Clean/Waste Water Tank	30L / 24 L 7.9 gal / 6.3 gal	
Gradeability	4.6°	
Min. Pass Width	800 mm 31.5 in	
Min. U-turn Width	1,100 mm 43.3 in	
Max. Cleaning Speed	1.2 m/s 2.7 mph	
Sensor System	2D LiDAR, 3D Depth Camera, RGB Camera, Anti-Collision Sensor, etc.	

*Note : [1]The specifications are derived from Gausium lab test results; actual performance data may vary in specific applications.
[2]Alternative configurations compliant with IEC 63327 are available upon request. Please note that the corresponding specifications may vary depending on the chosen configuration.

Award-Winning **Excellence**
Best-Selling Choice

INCLEAN
EXCELLENCE
AWARDS 2022

